

Service connection can be made more quickly if we do not have to set another power pole to reach yours.
*Connection can be mounted directly on the mobile home if 12" clearance to the weatherhead ...

The power company will give some service lines for free--for instance, from the road to a site 100 feet away.
But when you move beyond with many more poles and many more feet of wire ...

The wire inlets and outlets in the distribution box and switch box shall be set at the lower bottom of the box. It is strictly prohibited to set them at the top, side, back or door of the box.

PPL EU Requires a Satellite Dish be a minimum of 3 feet from PPL EU's facilities and maintain 50 inches of clearance space in front of the meter base. No attachments are permitted to the service ...

Slopes or uneven landscapes can change the vertical distance between a line and the ground. Because of these factors, the required height is often higher in areas where large machinery ...

Measure a horizontal 10 ft. line from the vertical plane mark in the direction of equipment/load to identify the Permit Zone boundary. Mark the Permit Zone Boundary with visible markers in a line parallel to ...

Adding a new building or modifying an existing one? Make sure to respect the clearance required from power lines. Here are the safe distances for each case.

Mobile homes served by underground distribution must provide meter pedestals for the connection of service laterals and watt-hour meters. A separate pedestal shall serve each mobile home as ...

Refer to the NEC for any required clearance distance of the ground rod away from the pedestal. The top of the ground rod may be exposed or buried as required to meet the applicable electric codes.

Recommended design vertical clearances for agency financed transmission lines of 230 kV and below are listed in the Tables 4-1 through 4-3. These clearances exceed the minimum clearances ...

Web: <https://www.idsolar.co.za>